

Rainbow Matt Finish Enamel

Rainbow Matt Finish is formulated to give an abrasion resistance paint film which is much more washable / Stain resistance than all kind of Plastic Emulsion with Silky look. It has non-glaring look which enables to hide the surface defects as Plastic Emulsion.

Specification:

Composition	Based on special Alkyd Resin, and inert pigments and Extenders for non-sagging application.
Thinner	Mineral Turpentine, quantity of Thinner depends on the method of application and surface.
Application	Spray, Brush, Roller
Covering Capacity	16-18 Sq/ Mtrs / Litter / Coat
Film Thickness	25-35 Micron
No. of Coats	In practice 2 coats gives complete obliteration on prepared surface.
Drying Time	1) Surface Dry 1-2 hours 2) Touch dry 2-3 hours 3) Recoatable 16 hours
Flash Point	Above 73°F
Gloss	Egg Shell Finish
Colour Range	As per Rainbow's Matt Finish Enamel Shade Card.
Packing	0.91 & 3.64 and 14.56 Ltrs.

Application Guide

New Concrete Surface

Sand down the plaster with emery stone and apply a coat of Rainbow Perfecton Wall Primer Sealer followed by putty. After surface is smooth and dry apply 2 Coats of Rainbow Matt Finish Enamel.

Steel Structure

Remove all dust, dirt and loose adhering or Flaked paints. Apply one coat of Rainbow Wall Primer Sealer followed by filling and then 2 coats of Rainbow Matt Finish Enamel.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
 North Karachi, Karachi.
 Ph: 021-36971166, 36971167, Cell: 0321-2111328
 Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
 Scheme No. 02, PF Chowk
 Tipu Road, Chaklala Rawalpindi
 Ph: 051-5590971, 051-5591436, 051-5961401