

## Rainbow Perfecton Wall Primer Sealer

Rainbow Wall Primer Sealer is an alkali sealer resisting Sealer and has been formulated with specially modified Alkyd Resin. This sealer provides a very good media for the preparation of high quality putty which can be safely used on wood, chip board, steel structure and all masonry work.

### Specification:

Composition	Special Binder combined with inert pigments and specially selected extenders.
Covering Capacity	12-14 Sq. Mtrs / litter / coat
Film Thickness	25-30 micron per coat
Number of Coats	One coat followed by filling for surface preparation.
Application	Brush, Roller, Spray (Preferably by Brush)
Drying Time	1) Surface Dry      1-2 Hours 2) Recoatable      16 Hours
Thinner	Mineral Turpentine
Gloss	Egg Shell to Matt
Flash Point	Above 73°F
Colour Range	White
Packing	0.91, 3.64 and 14.56 Ltrs

### Application Guide

#### New Surface

Apply one coat of wall primer sealer after sanding the plaster, followed by two coats of wall primer Sealer Putty.

#### Old Surface

Remove all the loose adhering paint by scraping and apply two coats of Wall Primer Sealer. First coat is used by slight over thinning, so that Sealer penetrates into the surface. Second coat helps further adhesion of Putty.

**Note:** The above Information is given in good faith, but without any warranty.

**Rainbow Paint Industries**

*Quality & Standard Paint Manufacturer*

#### Head Office:

CI-331, 16-B, Industrial Area,  
 North Karachi, Karachi.  
 Ph: 021-36971166, 36971167, Cell: 0321-2111328  
 Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

#### Regional Office:

House No. 5 Lane No. 1,  
 Scheme No. 02, PF Chowk  
 Tipu Road, Chaklala Rawalpindi  
 Ph: 051-5590971, 051-5591436, 051-5961401