



Rainbow Plastic Emulsion Paint

Rainbow Plastic Emulsion is a good Plastic Emulsion. It gives as smooth Velvety Finish and provides an extra edge in opacity and covering. It is suitable for both interior and exterior surfaces with or without any surface preparation.

This product is carefully formulated to suite the masonry work, Brick and Cement Renderings can also be applied on hard board and chip boards.

Specification:

Composition	Based on high quality polyvinyl acetate, acrylate resin combined with pigments and carefully selected extenders.
Covering Capacity	280-300 Sq. Fts / Gallon (complete covering).
Film Thickness	25-30 micron per coat
Number of Coats	2-3 on prepared surface
Application	Brush, Roller, Spray
Drying Time	Recoat after 2 hours
Thinner	Water 1:1
Gloss	Matt with silky finish
Colour Range	As per Rainbow's Plastic Emulsion Shade Card and or as required.
Packing	0.91, 3.64 and 14.56 Ltrs.

Application Guide

New Concrete Surface

Sand down the plaster with Emery Stone and apply one coat of Rainbow Perfecton Wall Primer Sealer. Prepare the surface by applying 2 coats of Putty prepared with Perfecton Wall Primer Sealer, apply 2-3 coats of Rainbow Plastic Emulsion Paint.

Old Painted Surface

Remove all dust, Dirt and loose adhering or flaked paints by scraping, apply one Coat of Rainbow Wall Primer Sealer with slight over thinning this will help Sealer to penetrate into the surface apply second coat of sealer followed by filling after the surface is properly prepared apply 2-3 coats of Rainbow Plastic Emulsion Paint.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401