

## Rainbow Red Oxide Primer

Rainbow Red Oxide Primer is formulated to suit tropical climate and economical to use. This is a perfect base for steel and wood to improve the adhesion of finish paint to substrate. This can also be used on Steel fabrication, machinery, Storage Tanks etc, which are to be left without finishing coat for sometime.

### Specification:

Composition	Alkyd Resin with Rust Resisting Pigments and carefully selected extenders.
Covering Capacity	15-18 Sq. Mtrs / Litter
Film Thickness	25-35 micron per coat
Number of Coats	2 Coats by brush or single coat by spray
Drying Time	S.D. 2 hours Recoatible 16 hours
Flash Point	Above 73°F
Thinner	Mineral Turpentine
Gloss	Matt Finish to Egg Shell
Colour Range	Red Oxide
Packing	0.91, 3.64 and 14.56 Ltrs.

### Application Guide

#### *New and unpainted surface*

All Dust, Dirt and Rust may be removed with wire Brush and paint should be applied immediately after cleaning.

#### *Old and Previous Painted Surface*

Remove all loose and flaking paint film with emery paper, and paint with Red Oxide Primer prior to finish coat

**Note:** The above Information is given in good faith, but without any warranty.

**Rainbow Paint Industries**

*Quality & Standard Paint Manufacturer*

#### Head Office:

CI-331, 16-B, Industrial Area,  
 North Karachi, Karachi.  
 Ph: 021-36971166, 36971167, Cell: 0321-2111328  
 Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

#### Regional Office:

House No. 5 Lane No. 1,  
 Scheme No. 02, PF Chowk  
 Tipu Road, Chaklala Rawalpindi  
 Ph: 051-5590971, 051-5591436, 051-5961401