

Rainbow Epoxy Primer

Rainbow Epoxy primer is developed to be used as a base coat for epoxy finishes.

Specification:

Composition	Epoxy resin / polyamide.
Application	Conventional / Airless spray
Covering	12 Sq. Meter / Ltrs.
Mixing Ratio	Paint 3 Volume, Hardener 1 Volume
Post life after Mixing	6 Hours
Dry time	S.D 2 Hours
	Recoatable 16 Hours
Film Thickness	30-35 Micron
Flash point	73°F
Application	Brush, Roller, Spray
Pack	Paint 3 Liters.
	Hardener 1 Liter.
Thinner	Epoxy thinner 890
Finish	Matt
Shelf Life	6 Months if Kept in sealed container at normal room temperature.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401