

Rainbow Interior Boiler Composition

Rainbow interior boiler composition is developed for all interior boiler drums, pipes and steam turbine casings.

Specification:

Composition	Graphite and Gilsonite
Application	Brush & Spray
Covering	8-10 Sq. Meter / Ltr.
No. of Coats	2 Coats at interval of 8 hours
Dry time	S.D 3-4 Hours
Film Thickness	25-30 Micron per coat
Flash point	73°C
Pack	3.64 & 14.56 Liters.
Thinner	Mineral turpentine
Colour	Black
Finish	Glossy
Surface Preparation	Remove all base mills scale & rust by sand blasting, in Case is not passable use mechanical tools or wire brushing.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401