



Rainbow Stoving Primer

Rainbow Stoving Primer is excellent Red oxide primer for good anti corrosion properties with or without phosphating.

Specification:

| | |
|-------------------|--|
| Composition | Dehydrated coaster oil alkyd and amino resin. |
| Covering Capacity | 10-12 sq. Meter / Litter (Single Coat) |
| Film Thickness | 25-30 Micron |
| Application | Conventional spray |
| Stoving Schedule | 30 Minutes at 120oc or 20 Minutes at 150oc PMT |
| Film Thickness | 25-30 Micron |
| Flash point | 73°F |
| Finish | Matt to Eggshell |
| Pack | 20 Liters Drum |
| Thinner | Stoving thinner 690 |
| Shelf life | 6 month if kept properly sealed container under normal room temperature. |

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401