

## Rainbow Polyurethane Enamel

Rainbow Polyurethane Enamel is a high gloss and extremely durable enamel for interior and exterior surfaces. Polyurethane enamel has excellent colour and gloss retention. This is specially recommended for coastal areas on concrete, steel & wooden surfaces.

### Specification:

#### Composition

Based on polyurethane resin (Single Pack)

#### Covering Capacity

16-18 Sq Meters /Ltrs./Coat.

#### Film Thickness

25-35 Micron per coat.

#### Application

: Brush, Roller, Spray

#### Number of Coats

: At least 2 coats should be applied for proper finish and durability

#### Drying Time

: 1) Surface Dry 1-2 Hours

: 2) Touch Dry 2-3 Hours

: 3) Recoatable 16 Hours

#### Thinner

Mineral Turpentine should be used for application depending on the Substrate and method of application.

#### Flash Point

Above 73°F

#### Gloss

Glossy with silky finish

#### Colour Range

Assorted colors

#### Packing

0.91, 3.64 and 14.56 Ltrs.

## Application Guide

### New Concrete Surface

Smoothen the surface by sand paper and apply a coat of Rainbow Synthetic under Coat followed by filling. After filling is dry sand paper the surface and apply 2 coats of P.U.E. In case the oil is coming out from the wood, remove oil by scraping and seal the oily portion by shellac solution prior to final painting.

### Old Painted Surfaces

Remove all the rust by sanding, rust removing solution or by flame, then apply one coat of Red Oxide Primer, Followed by 2 coats of Rainbow polyurethane Enamel.

Note: The above Information is given in good faith, but without any Warranty.

#### Head Office:

CI-331, 16-B, Industrial Area,  
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

**Rainbow Paint Industries**

*Quality & Standard Paint Manufacturer*

#### Regional Office:

House No. 5 Lane No. 1,  
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401