



Rainbow Superflex™ Exterior Wall Primer

Rainbow Superflex Exterior Wall Primer is a high performance elastomeric based emulsion highly washable and alkali resistant with extreme durability. It is able to bridge hairline cracks while offering fast drying and also stops seepage of water and gives good penetrative properties. This is to be used as primary coat to seal and enhance durability of finishing paint. It also contains effective additives which protect from fungus for many years. Superflex Exterior Wall Primer is an environmental friendly product which is completely free from harmful chemicals such as lead, solvent and mercury.

Specification:

Composition: Based on special pure acrylic emulsion with water proofing & extreme

durable properties, pigments & selected extenders.

Covering: 13 - 15 Sq.Meter/Liter/Coat (Depending on surface and nature of plaster)

Thinning Ratio | Depending on Surface & Application Method.

Application: Brush, Roller and Spray.

No of coats: Best result are achieved when two coats are applied

Thinner: | Water

Dry Time: 1-3 hours (Depending on the climatic conditions)

Film Tickness: 30 micron

Flash Point: Not Applicable

Colour: White

Finish: Matt

Packing: 0.91, 3.64 and 14.56 Ltrs.

Application Guide

New Surface

Sand down the plaster with emery paper preferably emery stone, apply one coat of Superflex Exterior Primer followed by, if required, Rainbow Superflex Exterior Putty. Two coats of putty is applied, with a interval of 2-3 hours between coats. Another coat of Superflex Exterior Primer can also be applied after Wall Putty application.

Old Surface

Remove dust, dirt and loose adhering or flaked paints by scarping with scraper (wall) or Emery Paper. Dust off and apply 1 coat of Superflex Exterior Primer. Allow to dry properly followed by, if required, 1-2 coats of Rainbow Superflex Exterior Putty. Prior to application of finish paint.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Head Office:

CI-331, 16-B, Industrial Area, North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Quality & Standard Caint Manufacturer

Regional Office:

Acturer House No. 5 Lane No. 1, Scheme No. 02, PF Chowk Tipu Road, Chaklala Rawalpindi Ph: 051-5590971, 051-5591436, 051-5961401