

Rainbow Weatherguard® Superflex™

Rainbow Weatherguard Superflex is a premium quality water-based elastomeric paint designed for exterior surfaces where extreme weather conditions are present. It can bridge minor hairline cracks while retaining its beauty. Superflex's Weather-Protect-technology can reduce temperature of your house by 4 to 5°C, provides more durability and resistance against dirt, dust and water. The paint features films that are extremely tolerant to elongation and contraction properties.

Weatherguard Superflex is an environmental friendly product which is completely free from harmful chemicals such as lead and mercury etc.

Recommended Uses:

Strongly recommended for exterior surfaces based on concrete, gypsum, wood, masonry, brickwork & plaster of houses, high rise towers, hotels etc.

Product Features:

- Crack Guard, bridges minor hairline cracks.
- Water vapor permeance & resists efflorescence.
- Temperature Guard (reduce temperature by 5°C).
- Superior hiding, water proofing, low VOC properties.
- Non-toxic, free from formaldehyde, Nickel, Lead & Mercury etc.
- UV Colourguard (resists colour fading with colour lock technology).
- Dirt, Dust & Water Guard.
- Bacteria & Fungus Guard.
- Superior weather resistance.

Specification:

Composition	Based on pure acrylic emulsion with water proofing & extreme durable properties and lightfast pigments.
Covering	13 – 15 Meter sq./liter/Coat
No. of Coats	3 – 4 Coats are required for better flexibility & cooling properties.
Dry Time	Minimum re-coatable time 2 hours
Film Maturity time	7 days minimum
Volume Solid	47- 49 % depending on colour
Gloss	Slight Sheen (Egg shell Finish)
Thinner	Water
Thinner Ratio	Depending on Surface & Application Method.
Application	Brush, Roller and Spray
Colour	Assorted /Shade Card
Packing	1 Liter, 4 Liter and 16 Liter
Shelf Life	Minimum shelf life for unopened, sealed paint is approximately 18 months when stored in a temperature controlled location.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.
Ph: 021-36971166, 36971167, Cell: 0321-2111328
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk
Tipu Road, Chaklala Rawalpindi
Ph: 051-5590971, 051-5591436, 051-5961401

<i>Application Guide</i>			
<i>Masonry</i>		<i>Wood</i>	<i>Metal</i>
<i>New Concrete Surface</i> Plaster must be completely dry (Approx 2 weeks are required for proper drying in normal climatic condition). Apply one coat Rainbow Elastomeric primer followed by 3 – 4 coats of Elastomeric Paint.	<i>Old Painted Surface</i> Remove all dust, dirt, oil, grease, mould, stain, loose and flaking paint before painting. Apply at least one coat of Rainbow Elastomeric Primer followed by 3 – 4 coats of Elastomeric Paints	Remove all oil, grease, wax polish and loose paint by scrapping. Fill gaps, seal knots and allow to dry. If necessary, wash with detergent and water followed by proper rinsing with fresh water and allow to dry.	Remove oil, grease, rust with detergent & water solution use waterproof emery paper if necessary. Allow to dry before applying Elastomeric Paint.
This paint is designed for masonry work but can also be applied on wood and metal.			
<i>Safety & Precautions</i>			
<ul style="list-style-type: none"> • Stir Paint vigorously prior to thinning. Avoid extra thinning • Make sure there is ample ventilation available before, during and after • Keep children and pets away from painted areas and appliances • When applying paint, it is preferable to wear eye safety goggles and dust mask • Never leave opened container unattended • To clean paint from your hands, use soap and water only 			
<i>Storage & Handling</i>			
<ul style="list-style-type: none"> • Keep away from heat and spark sources, away from direct sunlight. • Never breathe in dust, mist, gas or vapors from the dry product. • Keep the containers closed in storage. • Do not apply during rain/fog/mist/wind or when the temperature is below 5 °C. • In case of eye contact: Wash with plenty of cold water and immediately consult a physician. • In case of ingestion: drink plenty of water or milk, do not induce vomiting, & consult a doctor. • In case of inhalation: remove the person to open fresh air area, provide artificial breathing if needed, and consult a doctor. 			

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401