

Rainbow Passion Special Effect Paint

Rainbow Passion Special Effect paint is a premium quality decorative paint that is used to create fashionable and elegant walls with pearlescent finish. It is formulated to be used on all kind of masonry, concrete, wooden and gypsum surfaces. The product is a water-based product and can be diluteable by water to produce eye-catching decorative metallic effects. The product is highly washable and retains its original colour without blackening.

Rainbow Passion Special Effect Paint is an environmental friendly product which is completely free from harmful chemicals such as lead and mercury etc.

Recommended Uses:

Recommended for interior surfaces of concrete, wood, gypsum such as in restaurants, hotels, schools, lounges, bedrooms, hallways and as feature wall designs etc.

Product Features:

- Create fashionable and elegant work of art on walls. (Sparkle effect)
- Highly washable with long lasting colours.
- Low odour & low VOC.
- Hides plaster defects of the walls
- Environmental Friendly (free from formaldehyde, Nickel, Lead & Mercury etc.)
- Use a contrast base coat to achieve the most dramatic colour effects.

Specification:

Composition	Based on water reducible, non-yellowing binder combine with solid metallic pigment.
Covering	6-10 Meter Sq./Liter/Coat (Depending upon application)
No. of Coats	1-2 Coats on Prepared Surface.
Dry Time	1-2 Hours Recoatable: 4-6 Hours Under Normal Condition
Thinner/Cleaning	Water (Wash brush & other utensils with water)
Application	Brush, Roller, Spray, Trowel & Scraper (For painting & designing)
Thinner Ratio	Upto to 5% Maximum using water
Colours	Silver, Copper, Gold and other assorted colours as per shade card
Packing	100g, 1kg and 4 Kg
Shelf Life	Minimum shelf life for unopened, sealed paint is approximately 24 months when stored in a temperature controlled location.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.
Ph: 021-36971166, 36971167, Cell: 0321-2111328
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk
Tipu Road, Chaklala Rawalpindi
Ph: 051-5590971, 051-5591436, 051-5961401

Application Guide

New Concrete Surface

New plaster must be completely clean, dry and free from dirt and grease. Sand down the plaster with Emery stone or emery paper and apply one coat of Rainbow Water Based Primer. Prepare the surface by applying 2 coats of Rainbow Wall Putty. Then use Rainbow Water Based Primer as a base coat followed by 1-2 coats of Rainbow Passion Special Effect Paint. Use a white base coat to achieve the most dramatic color effects.

Old Painted Surface

Remove all dust, dirt and loose adhering or flaked paints by scarping with scraper (wall) or Emery Paper (for wooden surface). After scarping apply one coat of Rainbow Water Based Primer. Then apply second coat of Sealer which is followed by the Filling. For very old and powdery surface preferable to use Rainbow Wall Sealer Primer, followed by one coat of water based Primer. After the putty is completely dry, sand down the surface. After putty please use Rainbow Water Based Primer as a base coat followed by 1-2 coats of Rainbow Passion Special Effect Paint.

Safety & Precautions

- Stir Paint vigorously prior to thinning. Avoid extra thinning
- Make sure there is ample ventilation available before, during and after
- Keep children and pets away from painted areas and appliances
- When applying paint, it is preferable to wear eye safety goggles and dust mask
- Never leave opened container unattended
- To clean paint from your hands, use soap and water only

Storage & Handling

- Keep away from heat and spark sources, away from direct sunlight.
- Never breathe in dust, mist, gas or vapors from the dry product or the hot-melt.
- Keep the containers closed in storage.
- Do not apply during rain/fog/mist/wind or when the temperature is below 5 °C.
- In case of eye contact: Wash with plenty of cold water and immediately consult a physician.
- In case of ingestion: drink plenty of water or milk, do not induce vomiting, & consult a doctor.
- In case of inhalation: remove the person to open fresh air area, provide artificial breathing if needed, and consult a doctor.

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
 North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
 Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401