

Rainbow Tennis Court Paint

Rainbow Tennis Court Paint is a premium quality coating that is based on 100% acrylic emulsion. It provides a high quality non-slip surface coating for sports and recreational areas. Its highly balanced formula using specifically formulated advance quality acrylic resin, selected reinforced fillers with fungicides delivers an extremely durable adhesion, excellent colour retention, UV resistance and extraordinary wearing properties.

Product Uses:

Designed for use on bitumen and concrete such as indoor /outdoor tennis court, basketball courts, jogging paths and play area..

Product Features:

- High coverage with good weather-ability
- Excellent adhesion & Ultraviolet resistance
- High film build & durability
- Non-Slip & good foot grip
- Fungus & Algae resistant
- Non-fading & flexible Film

Specification:

Composition:	Based on high quality pure acrylic emulsion combined with durable pigments & inert extenders.
Covering:	8 – 10 Sq.Meter/Liter/Coat (Depending on surface and nature of surface)
Thinning Ratio	Depending on Surface & Application Method.
Application:	Brush, Roller and Spray.
No of coats:	2 to 3 coats should be applied for proper finish and durability.
Thinner:	Clean Drinkable Water
Dry Time:	3-4 hours (Dependent on temperature & humidity)
Film Tickness:	25-30 microns per coat
Flash Point:	Not Applicable
Colour:	Dark Green, Dark Blue, Terracotta
Finish:	Matt
Packing:	0.91, 3.64 Ltrs.
Shelf Life:	24 months approx(unopened, sealed & temperature controlled location)
Curing Time:	3 days
Clean-Up:	Clean equipment with water before curing.

Note: The above Information is given in good faith, but without any warranty.

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.
Ph: 021-36971166, 36971167, Cell: 0321-2111328
Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk
Tipu Road, Chaklala Rawalpindi
Ph: 051-5590971, 051-5591436, 051-5961401

Application Guide

Rainbow Tennis court is easily applied with a brush or roller, for better results apply 1st coat with 1:1 ratio (1 part RTC with 1 part water) and other coats apply thick as compare to 1st one to ensure a greater uniformity of coating thickness.

Surface Preparation:

The surface to be applied should be clean and free from any kind of contamination dirt, tar, oil, grease, bitumen coating also sound & free of fungus, mould & algae must be removed prior to application. Any existing coating must be inspected and adhesion tests carried out.

To obtain the best result before coating the floor, use a pressure washer or high pressure nozzle and water hose to wash the floor with a non-filming detergent. Use appropriate and take caution not to inject water into floor substrate.

Give the floor rinse to ensure it is free of all detergent or anything else that could affect adhesion.

Allow floor to dry completely before application. Using a blower or broom, clear any dust, dirt that may prevent proper adhesion.

Storage:

Store properly in a clean, covered and well-ventilated area. Storage outside this temperature range may shorten shelf life.

Safety & Precautions

- Stir Paint rigorously prior to thinning. Avoid extra thinning
- Make sure there is ample ventilation available before, during and after.
- Keep children and pets away from painted areas and appliances
- When applying paint, it is preferable to wear eye safety goggles and dust mask
- Never leave opened container unattended
- To clean paint from your hands, use soap and water only

Note: The above Information is given in good faith, but without any warranty.

Head Office:

CI-331, 16-B, Industrial Area,
North Karachi, Karachi.

Ph: 021-36971166, 36971167, Cell: 0321-2111328

Email: karachi@rainbow-paints.com, Web: www.rainbow-paints.com

Rainbow Paint Industries

Quality & Standard Paint Manufacturer

Regional Office:

House No. 5 Lane No. 1,
Scheme No. 02, PF Chowk

Tipu Road, Chaklala Rawalpindi

Ph: 051-5590971, 051-5591436, 051-5961401